




[HOME](#) [ABOUT DELPHION](#) [PRODUCTS](#) [NEWS & EVENTS](#) [IP RESOURCES](#) [IP RESEARCH](#)
[Patenting](#) [Prior Art](#) [Derwent](#) [Advanced](#) [Boolean](#) [Number](#) [Search](#)

[Search](#) [Login](#) [Register](#) [Order Form](#) [Shopping Cart](#) [Premium Features](#)



JP1282387A2:PRODUCTION OF ELASTIC POLYURETHANE YARN

[View Images \(1 pages\)](#) | [View INPADOC only](#) | [Derwent Record...](#)

JP Japan

YOSHIMOTO SEI
MURAMOTO YASUO

KANEBO LTD

[News, Profiles, Stocks and More about this company](#)

Nov. 14, 1989 / May 10, 1988

JP1988000113840

[D06M 13/38](#); [D06M 13/02](#); [D06M 15/643](#)

Purpose: To prevent the sticking of fibers immediately after spinning and to improve the unreeling property by compounding a conventional oiling agent with a polyorganosiloxane having a cyclic structure and a specific amine and feeding the obtained compounded oil in the production of an elastic polyurethane yarn.

Constitution: An elastic polyurethane yarn is produced by kneading a polyisocyanate prepolymer as a crosslinking agent. In the above process, said filament yarn is supplied with 1W10% of a compounded oil produced by mixing (A) a mineral oil and/or a straight-chain polyorganosiloxane (e.g., dimethylpolysiloxane) with (B) a polyorganosiloxane having a cyclic structure and (C) a diamine of formula (R2 is 1W5C alkyl; X is 0W5C alkylene, etc.). The sticking of the yarn on a spinning bobbin can be prevented by the applied oil to improve the unreeling of the yarn in the following process. The siloxane having a cyclic structure is e.g., a polyalkylsiloxane produced by hydrolyzing and condensing an alkyl-dihalogenated siloxane, etc.

COPYRIGHT: (C)1989,JPO&Japio

[Show known family members](#)

DERABS C89-375208 DERC89-375208

No patents reference this one

BEST AVAILABLE COPY

Alternative
Searches



[Patent Number](#)



[Boolean Text](#)



[Advanced Text](#)

Gallery of Patents

